

Exclusively from Safety Direct America!

SparkleTuff™ Anti-Slip *clear glossy floor coating*

At last you can have the flooring you love without fear of injuries due to slips, *WET OR DRY!* Tile, marble, granite, wood, vinyl, mosaic, etc. can meet and exceed OSHA- and ADA-compliant slip resistance (Coefficient of Friction, or COF) levels. **SparkleTuff™ Anti-Slip** is safe and easy to apply and is fully compatible with non-abrasive cleaning methods. **SparkleTuff™ Anti-Slip** has outstanding wear and chemical resistance, including resistance to acids and alkalis, and can also be used for underwater applications. It has excellent weathering and dirt pickup resistance and strong anti-corrosive characteristics.

SparkleTuff™ Anti-Slip coating retains its transparency and gloss far better than practically any other floor topcoat, including the best-of-breed epoxies and polyurethanes. **SparkleTuff™ Anti-Slip** does not require burnishing, and so less aggressive cleaning with safer cleaning agents and softer bristle pads or brushes is possible.

SparkleTuff™ Anti-Slip provides an abrasion-, stain- and water-resistant *glossy* finish that helps protect the coated surface from wear and damage while greatly reducing regular and costly maintenance such as stripping, polishing and waxing in a range of facilities including hospitals, swimming pools, schools, airports, restaurants, markets, hotels and resorts. When it is time to re-coat, simply add a fresh coat right over the existing coat. Quick and easy, once every 3 to 10 years depending on foot traffic. Properly applied and maintained, it will keep its slip resistance even when 500,000 – 1,000,000 people have walked over it! **SparkleTuff™ Anti-Slip** meets and exceeds the McDonalds Restaurants criterion for Sustainable Slip Resistance!

Save money — *no stripping or burnishing* means less floor maintenance labor and lower maintenance costs. An estimated 86% of floor care cost is labor. **SparkleTuff™ Anti-Slip** can eliminate up to 70% of that cost.

Sustainable — **SparkleTuff™ Anti-Slip** is a great way to make facilities more “green” compliant. Stripping, burnishing and re-waxing floors emits air pollutants, creates chemical by-products and waste and consumes precious commodities such as electricity and water.

SparkleTuff™ Anti-Slip, with its unique chemistry and composition, ease of use and outstanding durability is now the obvious coating of choice. Unlike other two-part coatings it has no VOCs, and virtually no unpleasant fumes or odors.

SparkleTuff™ Anti-Slip has a 75 minute working time after mixing. A 6-8 hour cure is recommended. At this time the coating will have hardened sufficiently to permit foot traffic and will have developed liquid- and stain-resistant properties. The chemical integration of the resin matrix will continue over the next 48 to 72 hours, at which time **SparkleTuff™ Anti-Slip** will achieve its optimal abrasion-, chemical- and weather-resistant properties!



Safety Direct America
The Anti-Slip Floor Superstore

1-800-988-6721
or 949-582-0889