



*clear glossy anti-slip floor coating for any floor type*

At last, you can have the flooring you love without fear of injuries due to slips, *WET OR DRY!* Tile, marble, granite, wood, vinyl, mosaic, terrazzo, concrete, tubs, pool decks, epoxy, etc. can meet and exceed OSHA- and ADA-compliant slip resistance (Coefficient of Friction, or COF) levels. **SparkleTuff™ Anti-Slip Floor Coating** is safe and easy to apply and is fully compatible with non-abrasive cleaning methods. SparkleTuff™ Anti-Slip has outstanding wear and chemical resistance, including resistance to acids and alkalis, and can also be used for underwater applications. It has excellent weathering and dirt pickup resistance and strong anti-corrosive characteristics. It's designed to last many, many years in commercial and industrial applications.



#### **SparkleTuff™ Anti-Slip Floor Coating**

retains its transparency and gloss far better than practically any other floor topcoat, including the best-of-breed epoxies and polyurethanes. SparkleTuff™ Anti-Slip Floor Coating will never yellow or crack and does not require burnishing. Less aggressive cleaning methods with safer cleaning agents and soft brushes is possible. It sticks to any floor, it's very anti-slip, it's extremely durable, and it looks great, too! Designed for nearly ANY application!

**SparkleTuff™ Anti-Slip Floor Coating** provides an abrasion-, stain- and water-resistant *glossy* finish that helps protect the coated surface from wear and damage while greatly reducing regular and costly maintenance such as stripping, polishing, and waxing in a range of facilities including hospitals, swimming pools, schools, airports, restaurants, markets, hotels and resorts. When it is time to re-coat, simply add a fresh coat right over the existing coat. Quick and easy, once every 5 to 10 years depending on foot traffic. Properly applied and maintained, it will keep its slip resistance even when 500,000 – 1,000,000 people have walked over it!

Save money — *no stripping or burnishing* means less floor maintenance labor and lower maintenance costs. An estimated 86% of floor care cost is labor. SparkleTuff™ Anti-Slip can eliminate up to 70% of that cost. Use a soft brush on an auto scrubber to clean, or a soft deck brush and a wet vacuum. Or simply use a soft brush and a hose to wash dirt into floor drains.

- Easy to apply by anyone
- Eliminates slips
- Clear, glossy, and extremely durable

Sustainable — SparkleTuff™ Anti-Slip is a great way to make facilities more “green” compliant. Stripping, burnishing, and re-waxing floors emits air pollutants, creates chemical by-products and waste and consumes precious commodities such as electricity and water.

Certified Slip Resistant by Every Slip Resistance Test Out There! Stop Slips Permanently!

Test Method	ANSI A137.1	ANSI B101.1	ANSI B101.3	ASTM C1028-07	Pendulum slip test (hard rubber)	Pendulum slip test (soft rubber)	Sustainable Slip Resistance
Safety Criterion	0.42	0.60	0.43	0.60	36	36	35
SparkleTuff Anti-Slip	0.83	≥1.00	0.81	0.90	63	45	61

**SparkleTuff™ Anti-Slip Floor Coating**, with its unique chemistry and composition, ease of use and outstanding durability is now the obvious coating of choice. Unlike other two-part coatings it has no VOCs, and virtually no unpleasant fumes or odors.

- 75-minute working time after mixing
- 8-hour cure is recommended for light foot traffic at 70°F. Allow more cure time for temperatures down to 55 degrees. SparkleTuff™ can be applied at even lower temperatures, but the cure time can take several days at temperatures below 50°F
- chemical integration of the resin matrix will continue over the next 48 to 72 hours, at which time SparkleTuff™ will achieve its optimal abrasion-, chemical- and weather-resistant properties.
- polysiloxane two-component coating with a long pot life
- apply only with supplied roller cover. Dispose of all used rollers, paint trays and buckets after use. Do not spill, and eye protection is highly advised during mixing and application.



#### Chemical Data

NVW (%): >99.0%  
 Appearance: Clear to Hazy Liquid  
 Visc. (cps): 1800  
 Flash Point: N/A  
 Chemical Stability: Stable  
 Density at 25°C: 1.14 g/cm  
 Storage: 50 - <80°F  
 Hazard Classification: Part A - Not Hazardous,  
 Part B - Acute toxicity, oral Category 4  
 Skin corrosion/irritation Category 1B  
 Serious eye damage/eye irritation Category 1

**SparkleTuff™ Anti-Slip Floor Coating** is available in gallons, quarts, and 8-ounce kits

Looks great – stops slips!