

# SparkleTuff™ Anti-Slip FLOOR COATING



At last, you can have the flooring you love without fear of injuries due to slips, *WET OR DRY!* Tile, marble, granite, wood, vinyl, mosaic, terrazzo, concrete, tubs, pool decks, epoxy, polyaspartic, polyurea, glass, etc. can meet and exceed OSHA- and ADA-compliant slip resistance (Coefficient of Friction, or COF) levels. **SparkleTuff™ Anti-Slip Floor Coating** is safe and easy to apply and is fully compatible with non-abrasive cleaning methods. SparkleTuff™ Anti-Slip has outstanding wear and chemical resistance, including resistance to acids and alkalis, and can also be used for underwater applications. It has excellent weathering and dirt pickup resistance and strong anti-corrosive characteristics. It's designed to last many, many years in commercial and industrial applications.



**SparkleTuff™ Anti-Slip Floor Coating** retains its transparency and gloss far better than practically any other floor topcoat, including the best-of-breed epoxies and polyurethanes. SparkleTuff™ Anti-Slip Floor Coating will never yellow or crack and does not require burnishing. Less aggressive cleaning methods with safer cleaning agents and soft brushes is possible. It sticks to any floor, it's very anti-slip, it's extremely durable, and it looks great, too! Designed for nearly ANY application!

**SparkleTuff™ Anti-Slip Floor Coating** provides an abrasion-, stain- and water-resistant glossy finish that helps protect the coated surface from wear and damage while greatly reducing regular and costly maintenance such as stripping, polishing, and waxing in a range of facilities including hospitals, swimming pools, schools, airports, restaurants, markets, hotels and resorts. When it is time to re-coat, simply add a fresh coat right over the existing coat. Quick and easy, once every 5 to 10 years depending on foot traffic. Properly applied and maintained, it will keep its slip resistance even when millions of people have walked over it!

**Looks great! Stops Slips!**



Save money — an estimated 86% of floor care cost is labor. SparkleTuff™ Anti-Slip can eliminate up to 70% of that cost. Use a soft brush on an auto scrubber to clean, or a soft deck brush and a wet vacuum. Or simply use a soft brush and a hose to wash dirt into floor drains.

- Easy to apply by anyone
- Eliminates slips
- Clear, glossy, and extremely durable

Sustainable — SparkleTuff™ Anti-Slip is a great way to make facilities more “green” compliant. Stripping, burnishing, and re-waxing floors emits air pollutants, creates chemical by-products and waste and consumes precious commodities such as electricity and water.

Certified Slip Resistant by Every Slip Resistance Test Out There! Stop Slips Permanently!

Test Method	Pendulum DCOF Test (hard rubber)	Pendulum DCOF Test (soft rubber)	Sustainable Slip Resistance	ANSI A326.3	ANSI B101.1	ANSI B101.3	ASTM C1028 SCOF
Safety Criterion	36	36	35	0.42	0.6	0.43	0.6
SparkleTuff Anti-Slip	73	63	71	0.75	0.98	0.73	0.92

**SparkleTuff™ Anti-Slip Floor Coating**, with its unique chemistry and composition, ease of use and outstanding durability is now the obvious coating of choice. Unlike other two-part coatings it has low VOC and low odor.

- 75-minute working time after mixing
- 8-hour cure is recommended for light foot traffic at 70°F. Allow more cure time for temperatures down to 55 degrees. SparkleTuff™ can be applied at even lower temperatures, but the cure time can take several days at temperatures below 50°F
- chemical integration of the resin matrix will continue over the next 48 to 72 hours, at which time SparkleTuff™ will achieve its optimal abrasion-, chemical- and weather-resistant properties.
- apply only with supplied roller cover. Dispose of all used rollers, paint trays and buckets after use. Do not spill, and eye protection is highly advised during mixing and application.



#### Chemical Data

NVW (%): >99.0%  
 Appearance: Clear to Hazy Liquid  
 Visc. (cps): 45000  
 Flash Point: N/A  
 Chemical Stability: Stable  
 Density at 25°C: 1.14 g/cm  
 Storage: 50 - <80°  
 VOC < 50 g/L



**SparkleTuff™ Anti-Slip Floor Coating** is available in gallons, quarts, and 8-ounce kits

**IMPORTANT:** Designed to be mixed with other components. The mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions. **KEEP OUT OF REACH OF CHILDREN.** Refer to attached health and safety instructions. Refer to Safety Data Sheet for additional health and safety information.

**Looks great! Stops Slips!**



## Health & Safety Warnings

Part A	Part B
<p style="text-align: center;"><b>WARNING!</b> CAUSES EYE IRRITATION</p> <p><b>CONTAINS: Cyclohexanol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane</b></p> <p>CAUSES EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION.</p> <p><b>Use only with adequate ventilation.</b> Do not breathe vapors or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes, skin and clothing. Wear chemical resistant goggles and face shield, chemical resistant gloves and protective clothing during application and cleanup. Do not permit anyone without protection in the painting area. Close container after each use. Wash thoroughly after handling.</p> <p> <b>WARNING:</b> This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>.</p> <p><b>FIRST AID:</b> In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately. In case of skin contact, immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation persists. In case of ingestion, <b>DO NOT INDUCE VOMITTING</b>, get medical attention immediately. If affected by inhalation of vapors or sanding dust, remove to fresh air.</p> <p><b>IN CASE OF SPILL:</b> Absorb with inert material and dispose of in accordance with applicable regulations.</p> <p>USE COMPLETELY OR DISPOSE OF PROPERLY. <b>Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.</b></p>	<p style="text-align: center;"><b>DANGER!</b> COMBUSTIBLE LIQUID AND VAPOR CORROSIVE HARMFUL IF SWALLOWED CAUSES EYE AND SKIN BURNS</p> <p><b>CONTAINS: gamma-Aminopropyltriethoxysilane</b></p> <p>CAUSES BURNS OF EYE, SKIN AND MUCOUS MEMBRANES. HARMFUL IF SWALLOWED. HARMFUL BY INHALATION. MAY CAUSE ALLERGIC SKIN REACTION.</p> <p>Keep away from heat and flame. <b>Use only with adequate ventilation.</b> Do not breathe vapors or sanding dust. Avoid contact with eyes, skin and clothing. Wear chemical resistant goggles and face shield, chemical resistant gloves and protective clothing during application and cleanup. Do not wear contact lenses. Open doors, windows or use other means to ensure fresh air entry during application and cleanup. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor levels are above the applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. Wash thoroughly after handling. Close container after each use.</p> <p> <b>WARNING:</b> This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>.</p> <p><b>FIRST AID:</b> If affected by inhalation of vapors or sanding dust, remove to fresh air and get medical help immediately. In case of eye contact, flush immediately with copious amounts of water holding eyelids open for at least 15 minutes and get medical attention immediately. In cases of skin contact, remove contaminated clothing and flush affected area with water for at least 15 minutes, get medical help immediately. If swallowed, <b>DO NOT INDUCE VOMITING</b>, get medical help immediately.</p> <p><b>IN CASE OF FIRE</b> – Use foam, CO<sub>2</sub>, dry chemical or water fog. <b>SPILL</b> – Absorb with inert material and dispose of as specified below.</p>

Part A	Part B
	<p>USE COMPLETELY OR DISPOSE OF PROPERLY. This product contains chemicals which may cause adverse effects to the environment if handled improperly. Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.</p> <p>Disposal of wastes containing either chemicals or free-liquids in landfills is prohibited. <b>Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for local disposal options.</b></p>

**KEEP OUT OF REACH OF CHILDREN**

**Refer to Safety Data Sheet for additional health and safety information.**

---

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Made in the USA with US and globally sourced materials.